



Type 2270 Level Sensors, Continuous Measuring, Blind Version, 4-20 mA / HART Output

- Principle: non-contact ultrasonic transit time
- Measuring range: 0.2...4 m, 0.25...6 m
- Sensor Type: PP or PVDF
- Output: 4-20 mA, 2-wire; HART Protocol
- Supply power: 12...36 V DC

MFR #	Measuring range (m)	Process Connection	Sensor Type
2270-P-1B-4	0.20 - 4.00	1 1/2" BSP	PP
2270-P-1B-6	0.25 - 6.00	2" BSP	PP
2270-P-1N-8	0.35 - 8.00	2" BSP	PP
2270-V-1B-4	0.20 - 4.00	1 1/2" BSP	PVDF
2270-V-1B-6	0.25 - 6.00	2" BSP	PVDF
2270-V-1N-8	0.35 - 8.00	2" BSP	PVDF
2270-P-1N-4	0.20 - 4.00	1 1/2" NPT	PP
2270-P-1N-6	0.25 - 6.00	2" NPT	PP
2270-P-1B-8	0.35 - 8.00	2" NPT	PP
2270-V-1N-4	0.20 - 4.00	1 1/2" NPT	PVDF
2270-V-1N-6	0.25 - 6.00	2" NPT	PVDF
2270-V-1B-8	0.35 - 8.00	2" NPT	PVDF

Code	Weight (kg)	PF
159 300 155	0.790	3 86 375 010
159 300 156	0.790	3 86 375 010
159 300 116	0.790	3 86 375 010
159 300 162	0.790	3 86 375 010
159 300 163	1.040	3 86 375 010
159 300 117	0.790	3 86 375 010
159 300 169	0.790	3 86 375 010
159 300 170	0.790	3 86 375 010
159 300 111	0.790	3 86 375 010
159 300 176	0.790	3 86 375 010
159 300 177	0.790	3 86 375 010
159 300 115	0.790	3 86 375 010

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>